



(19)

Generated Document.

(11) Publication number: **03185817 A**

# PATENT ABSTRACTS OF JAPAN

(21) Application number: 01325034

(51) Int. Cl.: H01L 21/205 H01L 21/263

(22) Application date: 15.12.89

(30) Priority:

(43) Date of application publication: 13.08.91

(84) Designated contracting states:

(71) Applicant: SEIKO EPSON CORP

(72) Inventor: IWAMATSU SEIICHI

(74) Representative:

## (54) METHOD OF FORMING SEMICONDUCTOR FILM

(57) Abstract:

PURPOSE: To enable polycrystalline Si film growth and epitaxial growth of large mobility at a low temperature, by forming an Si film on a substrate by using thermal decomposition or optical decomposition of specified silane material.

CONSTITUTION: An Si film is formed on a substrate by thermally or optically decomposing raw material of

silane ( $\text{SiH}_{2n+2}$ ),  $n = 3$ , like trisilane ( $\text{Si}_3\text{H}_8$ ) and tetrasilane ( $\text{Si}_4\text{H}_{10}$ ). By CVD method, a polycrystalline Si film whose grain diameter is about  $3\mu\text{m}$  can be formed when the temperature of a Pyrex glass substrate is  $400^\circ\text{C}$ . A TFT using an Si film has large electric charge mobility and high speed operation is realized. The similar polycrystal can be obtained by irradiating the surface of the substrate at  $100^\circ\text{C}$  with ultraviolet rays. In order to epitaxially grow a single crystal Si film on a single crystal Si substrate by using  $\text{Si}_3\text{H}_8$  or  $\text{Si}_4\text{H}_{10}$  as raw material, the substrate temperature is set at  $100^\circ\text{C}$ , and ultraviolet rays are projected or plasma is utilized.

COPYRIGHT: (C)1991, JPO&Japio